

KPEL 9K DIFFERENTIAL PRESSURE TRANSMITTER

KPEL 9K is a pressure transmitter for detecting pressures and pressure differences of the air-handling system.

The transmitter has two separate temperature compensated pressure measurements. The pressure range can be selected separately for both measurements.

To order a transmitter with backlit display, add "-N" to the model (e.g. KPEL 9K-N). The display resolution is 1 Pa. The display can also be added after commissioning.


The transmitter can also be used as a controller. The controller settings can be changed by using the ML-SER tool.

Selecting measuring range

S1/S4	S2/S5	S3/S6	
		■	●●
■	■	0...9000 Pa *	0...5000 Pa
●●	■	0...8000 Pa	0...4000 Pa
■	●●	0...7000 Pa	0...3000 Pa
●●	●●	0...6000 Pa	0...2000 Pa

* = Factory setting. The 0...9000 Pa range is also used for the custom range setting. The range limits can be changed with the ML-SER tool.

Wiring



Technical data:

Supply	24 Vac/dc (22...28 V)	
Power consumption	24 Vdc < 2,0 VA 24 Vac < 2,5 VA	
Measuring ranges	0...2000 Pa	0...6000 Pa
	0...3000 Pa	0...7000 Pa
	0...4000 Pa	0...8000 Pa
	0...5000 Pa	*0...9000 Pa
Pressure connections	Ø5 mm	
**Outputs	2 x 0...10 Vdc, < 2 mA or 2 x 4...20 mA, < 700 Ω	
Accuracy	±10 Pa ±1.25 % of reading (25 °C)	
Long term stability	±20 Pa/year	
Time constant	1...20 s, *4 s	
Display (N models)	backlit dot matrix display	
Operating temperature	0...50 °C	
Max. over pressure	25 kPa	
Housing	IP54, polycarbonate	
	* = factory setting	
	** = Two terminals for outputs	

Ordering guide:

Model	Product number	Description
KPEL 9K	1131330	dual differential pressure transmitter; manual zeroing
ML-SER	1139010	Transmitter commissioning tool

Products fulfill the requirements of directive 2004/108/EC and are in accordance with the standards EN61000-6-3 (Emission) and EN61000-6-2 (Immunity).