

FLOOR HEATING / COOLING CONTROLLER HLS 16

HLS 16 is a 1-stage floor heating / cooling controller for individual room temperature control. Both heating and cooling are controlled by using the same thermal actuator. The cooling or heating function can be selected with the external contact connected to the terminal Z1. (Z1= off = heating or Z1=Go=cooling)

The controller supports thermal actuators (NO or NC). The actuators are controlled time proportionally in about 20 second sequences.

Room temperature is detected by an internal NTC10 sensor. The output, controlling heating (red light) and cooling (green light), is proportional to the difference between set point and measured value.


Normally the display of HLS 16-N indicates the detected value, but when the setting has been changed it will be indicated for 2 s.

Jumper settings:

S1	Valve jam prevention		Valve jam prevention on
		• •	Valve jam prevention off
S2	Proportional band (Xp)		2 °C
		• •	1 °C
S3	Centre of user set point area	The user set point area centre (factory setting 21 °C) can be changed by turning the potentiometer to the desired position and then removing and replacing the jumper.	

Wiring

Thermal actuator, NO Thermal actuator, NC





Technical data:

Supply 24 Vac (20...28 V) / 1 VA Set point 18...24, ±3 °C, *21 °C

Accuracy (measurement) ±0.5 °C 0...3 °C. *0.0 °C Dead zone (Dz) Proportional band (Xp) 1 °C or *2 °C 24 Vac, 1 A Outputs A1 and A2

Operating conditions temperature

0...50 °C 0...85 % RH (non-condensing) humidity

Terminals 1,5 mm² Housing ABS plastic, IP20

on the wall or on the standard flush Mounting mounting box (60 mm hole distance)

* = factory settings

Ordering guide:

Model Product number Description floor heating / cooling HLS 16 1150160 controller HLS 16-N 1150161 floor heating / cooling controller with display

Products fulfill the requirements of directive 2004/108/EC and are in accordance with the standards EN61000-6-3 (Emission) and EN61000-6-2 (Immunity).