

ILK - DUCT AIR QUALITY TRANSMITTER/CONTROLLER

ILK transmitters are designed for detecting and controlling VOC (Volatile Organic Compound) level, temperature and humidity inside ventilation ducts. MEMS sensing technology ensures accurate and durable VOC measurement that is related to the CO₂ level. With the VOC level information the demand based ventilation can be controlled effectively.


The VOC sensor detects wide variety of hydrocarbons such as cigarette smoke, exhaled breathing air, solvent vapours, building material emissions and cleaning agent vapours.

The measurement values scroll on the N model display. The wanted value can be locked to view continuously.

The control output can be controlled either according to a one measurement value or according to the maximum selection of all values. The controller settings can be changed by using the ML-SER tool.

The transmitter can be equipped with a HD-R relay (24 Vac, 1 A). The relay output can be controlled either according to a one measurement value or according to the all measured values. The relay switching point can be adjusted by using ML-SER tool.

Wiring:





Technical data

Supply 24 Vac/dc (22...28 V) < 2 W

VOC measurement

range 450...2000 ppm (CO₂ equivalent)

warm up time 15 m

output 0...10 V < 2 mA = 0...2000 ppm

Temperature measurement

range 0...50 °C accuracy (25 °C) ± 0.5 °C

output $0...10 \text{ V} < 2 \text{ mA} = 0...50 ^{\circ}\text{C}$

Humidity measurement (RH models)

range 0...100 %rH accuracy (25 °C) ±2 %rH

output 0...10 V < 2 mA = 0...100 %rH

Control output 0...10 V < 2 mA

Measuring probe Ø 10 mm x 110 mm;
duct insulation < 75 mm

Operating conditions

temperature 0...+50 °C

humidity 0...85 % RH (non cond.)

Housing IP54

Dimensions (w x h x d) 105 x 104 x 155 mm

Ordering guide:

,	Ji dering guide.		
N	Model	Product number	Description
	LK	1135630	VOC and °C duct transmitter
	LK-N	1135631	duct transmitter with display
	LK-RH	1135632	VOC, °C and %rH duct transmitter
	LK-RH-N	1135633	duct transmitter with display
ŀ	HD-R	1135003	option, relay 24 Vac 1 A
1	ML-SER	1139010	transmitter commissioning tool

Products fulfil the requirements of directive 2004/108/EC and are in accordance with the standards EN61000-6-3: 2001 (Emission) and EN61000-6-2: 2001 (Immunity).

